BC BUILDING CODE INTERPRETATION COMMITTEE AIBC, APEGBC, BOABC, POABC

File No: 06-0003	INTERPRETATION	Page 1 of 1	
Interpretation Date:	October 16, 2007		
Building Code Edition:	BC Building Code 2006	BC Building Code 2006	
Subject:	Hinged Skylight Access	Hinged Skylight Access to Roof Deck	
Keywords:	Access, Roof Access	Access, Roof Access	
Building Code Reference(s):		3.3.1.3.(3), 3.3.1.13.(4), 3.3.4.7.(1), 9.7.7, 9.8., 9.9.6.7.(1)(a), 9.9.7.1.(1)	

Question:

Is a spring-loaded hinged skylight or roof hatch at the top of the stair an acceptable means of providing access to and egress from an occupied roof deck serving one dwelling unit?

Interpretation:

Yes, with provisions.

Sentences 3.3.1.3.(3) and 9.9.7.1.(1) require that an access to exit shall be provided from every roof intended for occupancy.

Part 3 and Part 9 of the Building Code do not prohibit the use of a skylight or a roof hatch as providing access to or egress from the roof deck.

A spring-loaded hinged skylight or roof hatch is an acceptable means of providing access to and egress from an occupied roof deck serving a dwelling unit provided the stair, handrails and guards including the guard around the opening of the hinged skylight, comply with Sentence 3.3.4.7.(1) and Section 9.8; and its opening mechanism comply with Sentence 3.3.1.13.(4) and Clause 9.9.6.7.(1)(a).

R. J. Light, Committee Chair

The views expressed are the consensus of the joint committee of AIBC, APEGBC, BOABC, and POABC, which form the BC Building Code Interpretation Committee. The purpose of the committee is to encourage uniform province wide interpretation of the BC Building Code. These views should not be considered as the official interpretation of legislated requirements based on the BC Building Code, as final responsibility for an interpretation rests with the local *Authority Having Jurisdiction*. The views of the joint committee should not be construed as legal advice.